Sulfiwine K 150

SULFUROUS PRODUCTS

Always take into consideration the legal maxima for sulphur dioxide (S0 $_{
m 21}$ in wine

Enological applications

SULFIWINE K 150 is potassium bisulphite at 150 g/L. SULFIWINE K 150 can be used throughout the wine making process from pressings to must to finished wine.

- On must : In the must reception tank, to prevent oxidasic casse and all microbial alterations.
- For red wines: At vatting, during crushing for extracting and fixing colouring matter.

SULFIWINE K 150 has the following properties:

- It prevents the development of microbic agents via its antiseptic role.
- It is a selective factor for yeasts by limiting the development of undesirable yeasts.
- By activating an antioxidant it plays a preventative role against oxidasic casse.
- It facilitates colour extraction by promoting extraction of anthocyanins contained in the skin.
- It enables colour fixation in red wines.

Instructions for use

Homogenize properly after addition in wine or must. Avoid contact with metallic items (iron, copper or aluminium).

Dose rate

Up to 7 cL/hL depending on vinification conditions Consult your oenologist or laboratory.

Packaging and storage

COD. EXP77150240 - 12 kg and 24 kg cans.

Store in a dry environment which is well ventilated at a temperature between 10 and 20 °C. The recommended use by date is marked on the packaging. SULFIWINE K 150 rapidly loses its effectiveness once the package has been opened.



Via Salvo D'Acquisto, 2 - 37036 S. Martino Buon Albergo (VR) Italy tel. +39-045-8788611 r.a. fax +39-045-8780322 fax uff. vendite +39-045-8780122 www.perdomini-ioc.com - info@perdomini-ioc.com